



Suspended seat.

Structure:

- natural or wengé dyed ash wood, finished with a matt transparent acrylic wax and treated to be anti-mould
- matt or gloss varnished in the colours in the collection (reference for colours: Mano Lucida wood sample collection).

A seat pad and a loose cushion are necessary for complete seating comfort.

Seat pad: removable, in open cell polyurethane covered with three dimensional polyester fabric.

Loose cushion: removable, in recycled and biodegradable polyester fibre, fixed cover in waterproofed polyester.

Seat pad and cushion upholstery: removable and available in the outdoor fabrics listed here below.

Suspension cords: AISI 316 stainless steel covered with a braid in cemento colour and provided of clamps and hooks in AISI 316 stainless steel for the suspension to ceiling or to a beam.


Notes:

Swing can also be hanged to a specific structure made of AISI 304 stainless steel, matt varnished in avorio or grafite basic colours, matt or gloss varnished in the colours in the collection (reference for colours: Mano Lucida wood sample collection). The structure is complete of base plates for the fixing to weight bearing surfaces.


The wood used for Swing can be used in exterior environments, but cannot be directly exposed to the elements; therefore it is necessary to use Swing in a permanently covered area and protect it with the Winter Set cover during the night. Furthermore, when the seat is not used for prolonged periods of time, it is necessary to shelter it in a closed space.

We advise to use a Winter Set protection cover.

B65B natural/wengé



B65C mano lucida



B65S

